

QUALITATIVE FIT TEST RECORD

A medical evaluation must be completed by the employee and approved for respirator wear prior to conducting the qualitative fit test.

Energy Efficiency Specialists™

(See testing procedures on reverse side)

Employee Information		
Employee Name: Lincoln Caldwell D	ate: 2-17-22	
Job Title: Insulator Divis	sion: $2 \cdot P \wedge x$	
Date Medical Evaluation Completed: 2 - 17 - 2022 Med	ically Cleared: YES NO	
Respirator and Filter Data		
☐ Dust Mask ☐ Air Purifying ☐ Supplied Air ☐ S	CBA PAPR	
Respirator Make: Honeywell Model: OV/R95	Size: Medium	
Filter Type: Honeywell 7583P100L NIOSH Approval #: 84A - 0600		
Test Agent		
☐ Irritant Smoke ☐ Isoamyl Acetate ☐ Bitrex	Saccharin Mist	
Conditions		
☐ Clean Shaven ☐ Facial Scar ☐ Dentures ☐ G	lasses PPE Worn	
Comments:		
Fit Test Exercises		
1. Initial fit ok?	Pass Fail	
Positive pressure check	Pass Fail	
3. Negative pressure check	Pass Fail	
4. Fit Test Exercises		
a. Normal breathing (1 min)	Pass Fail	
b. Deep breathing (1 min)	Pass Fail	
c. Turning head side to side (1 min)	Pass Fail	
d. Moving head up and down (1 min)	Pass Fail	
e. Talking / Reading (1 min)	Pass Fail	
f. Bend over or jog in place (1 min)	Pass Fail	
5. Fit satisfactory?	Satisfactory Unsatisfactory	
Print Name Signature	Date:	
Employee Lincoln CALDWGLL Jouch Calg	Well 2/17/22	
Tester John Nold Andl	2-17-22	

Testing Procedures

- 1. Insure no beards, sideburns, mustaches, stubble or hair will affect the sealing surface.
- 2. Put on the respirator
 - a. Position the respirator on the face
 - b. Set strap tension
 - c. Determine an acceptable fit
- 3. Check for comfort by insuring room for eye protection, room to talk, position on face and cheeks.
 - a. Anytime during the testing procedure, if the respirator must be refitted to face, the test is void and must be started over.
- 4. Complete positive pressure check.
 - a. Close off the exhalation valve and exhale gently into the facepiece. The fit is considered satisfactory if a slight positive pressure can be built up inside the facepiece without any evidence of outward leakage of air at the seal. For most respirators, this method of leak testing requires the wearer to first remove the exhalation valve cover before closing off the exhalation valve and then carefully replacing it after the test.
- 5. Complete negative pressure seal check.
 - a. Close off the inlet opening of the canister or cartridge(s) by covering with the palm of the hand(s) or by replacing the filter seal(s), inhale gently so that the facepiece collapses slightly, and hold the breath for 10 seconds. Since the design of the inlet opening of some cartridges cannot be effectively covered with the palm of the hand, the test can be performed by covering the inlet opening of the cartridge with a thin latex or nitrile glove. If the facepiece remains in its slightly collapsed condition and no inward leakage of air is detected, the tightness of the respirator is considered satisfactory.
- 6. **Normal breathing:** have wearer breathe normally for 1 minute in a standing position without talking.
- 7. **Deep Breathing:** have wearer breathe slowly and deeply for 1 minute in a standing position without talking.
- 8. **Turning head side to side:** have wearer turn their head from side to side at extreme positions for 1 minute
- Moving Head up and down: have wearer move their head up and down at extreme positions for 1 minute
- 10. **Talking:** have wearer talk out loud slowly and loud enough for tester to hear clearly for 1 minute or have them count down from 100.

Rainbow Passage

When the sunlight strikes raindrops in the air, they act like a prism and form a rainbow. The rainbow is a division of white light into many beautiful colors. These take the shape of a long round arch, with its path high above, and its two ends apparently beyond the horizon.

There is, according to legend, a boiling pot of gold at one end. People look, but no one ever finds it. When a man looks for something beyond reach, his friends say he is looking for the pot of gold at the end of the rainbow.

- 11. **Bending over / jogging in place:** have wearer bend over at the waist as if to touch the toes for 1 minute, if unable have employee jog in place for 1 minute
- 12. To maintain an adequate concentration of aerosol during this test, inject ½ the number of squeezes (5,10,15) every 30 seconds for the duration of the fit test.
- 13. The test is terminated at any time the bitter taste of aerosol is detected by the employee.
- 14. If the entire test is completed without the employee detecting the bitter taste of the aerosol, the test is successful and respirator fit has been demonstrated.

Did the wearer complete all the above requirements?	YES	NO
The respirator fit test is:	Satisfactory	Unsatisfactory
Reason for failure (if applicable):		<u> </u>