

Safety Data Sheet

Copyright,2018,3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group: 39-5031-8 **Version Number:** 1.00

Issue Date: 08/24/18 **Supercedes Date:** Initial Issue

Product identifier

6029PP 3M™ ESPE™ FILTEK™ SUPREME ULTRA UNIVERSAL RESTORATIVE PILLOW PACK

ID Number(s):

70-2010-8803-9, 70-2014-1299-9

7000129006, 7100156379

Recommended use

Dental Product, Dental Restorative

Restrictions on use

For use only by Dental Professionals

Supplier's details

MANUFACTURER: 3M

DIVISION: Oral Care Solutions Division

ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA

Telephone: 1-888-3M HELPS (1-888-364-3577)

Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet (SDS), Article Information Sheet (AIS), or Article Information Letter (AIL) for each of these components is included. Please do not separate the component documents from this cover page. The document numbers for components of this product are:

26-5783-1, 27-9483-2, 29-8287-4

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued.3MMAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3Mproduct is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3Mproduct, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3Mproduct to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3Mprovides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may

6029PP 3MTM ESPETM FILTEKTM SUPREME ULTRA UNIVERSAL RESTORATIVE PILLOW PACK

08/24/18

have resulted in errors, omissions or alterations in this information,3Mmakes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from3M

3M USA SDSs are available at www.3M.com



Safety Data Sheet

Copyright, 2020, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 29-8287-4
 Version Number:
 7.02

 Issue Date:
 02/21/20
 Supercedes Date:
 06/05/19

SECTION 1: Identification

1.1. Product identifier

3MTM ESPETM ScotchbondTM Universal

Product Identification Numbers

LE-F100-1014-6, LE-F100-1014-7, LE-F100-1014-9, 70-2011-3903-0 7000055178

1.2. Recommended use and restrictions on use

Recommended use

Dental Product, Adhesive

Restrictions on use

For use only by dental professionals.

1.3. Supplier's details

MANUFACTURER: 3M

DIVISION: Oral Care Solutions Division

ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA

Telephone: 1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

2.1. Hazard classification

Flammable Liquid: Category 3.

Serious Eye Damage/Irritation: Category 1.

Skin Sensitizer: Category 1.

2.2. Label elements

Signal word

Danger

Symbols

Flame | Corrosion | Exclamation mark |





Hazard Statements

Flammable liquid and vapor.

Causes serious eye damage.

May cause an allergic skin reaction.

Precautionary Statements

Prevention:

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Take precautionary measures against static discharge.

Keep container tightly closed.

Wear protective gloves and eye/face protection.

Contaminated work clothing must not be allowed out of the workplace.

Response:

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER or doctor/physician.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

Storage:

Store in a well-ventilated place. Keep cool.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Hazards not otherwise classified

May cause chemical gastrointestinal burns.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
2-HYDROXYETHYL METHACRYLATE	868-77-9	15 - 25 Trade Secret *
BISPHENOL A DIGLYCIDYL ETHER	1565-94-2	15 - 25 Trade Secret *
DIMETHACRYLATE (BISGMA)		
2-PROPENOIC ACID, 2-METHYL-, REACTION	1207736-18-2	10 - 20 Trade Secret *
PRODUCTS WITH 1,10-DECANEDIOL AND		
PHOSPHOROUS OXIDE (P2O5)		

Page 2 **of** 11

3MTM ESPETM ScotchbondTM Universal	02/21/20	
3 VIIM R.SPRIM Scotchhondim I Iniversal	02/21/20	

ETHANOL	64-17-5	10 - 15 Trade Secret *
WATER	7732-18-5	10 - 15 Trade Secret *
COPOLYMER OF ACRYLIC AND ITACONIC ACID	25948-33-8	1 - 5 Trade Secret *
CAMPHORQUINONE	10373-78-1	< 2 Trade Secret *
DIMETHYLAMINOBENZOAT(-4)	10287-53-3	< 2 Trade Secret *

^{*}The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If Swallowed:

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance	<u>Condition</u>
Formaldehyde	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Irritant Vapors or Gases	During Combustion
Oxides of Nitrogen	During Combustion

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering

for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire-extinguishing foam designed for use on solvents, such as alcohols and acetone, that can dissolve in water. An AR - AFFF type foam is recommended. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with detergent and water. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

A no-touch technique is recommended. If skin contact occurs, wash skin with soap and water. Acrylates may penetrate commonly-used gloves. If product contacts glove, remove and discard glove, wash hands immediately with soap and water and then re-glove. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Take precautionary measures against static discharge. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Do not get in eyes.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from heat. Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments	
ETHANOL	64-17-5	ACGIH	STEL:1000 ppm	A3: Confirmed animal carcin.	
ETHANOL	64-17-5	OSHA	TWA:1900 mg/m3(1000 ppm)		

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

OSHA: United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use in a well-ventilated area.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Safety Glasses with side shields

Skin/hand protection

See Section 7.1 for additional information on skin protection.

Respiratory protection

None required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical stateLiquidColorYellow

Specific Physical Form:Viscous LiquidOdorCharacteristic OdorOdor thresholdNo Data AvailablePHNot ApplicableMelting pointNo Data Available

Boiling Point >= 78 °C

Flash Point 30.5 °C [Test Method: Closed Cup]

Evaporation rateNo Data AvailableFlammability (solid, gas)Not ApplicableFlammable Limits(LEL)No Data AvailableFlammable Limits(UEL)No Data AvailableVapor PressureNo Data AvailableVapor DensityNo Data AvailableDensity1 - 1.2 g/cm3

Specific Gravity 1 - 1.2 [Ref Std:WATER=1]

Solubility in Water Appreciable No Data Available Solubility- non-water Partition coefficient: n-octanol/ water No Data Available **Autoignition temperature** No Data Available **Decomposition temperature** No Data Available Not Applicable Viscosity Molecular weight No Data Available **Volatile Organic Compounds** No Data Available

SECTION 10: Stability and reactivity

10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

02/21/20

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

Substance
None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure. The information below represents toxicological information associated with the individual components of the uncured product. Once properly mixed and/or cured, the product is safe for its intended use.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

No health effects are expected.

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eve Contact:

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion:

Gastrointestinal Corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain; nausea; vomiting; and diarrhea; blood in the feces and/or vomitus may also be seen.

- .

Additional Information:

This product contains ethanol. Alcoholic beverages and ethanol in alcoholic beverages have been classified by the International Agency for Research on Cancer as carcinogenic to humans. There are also data associating human consumption of alcoholic beverages with developmental toxicity and liver toxicity. Exposure to ethanol during the foreseeable use of this product is not expected to cause cancer, developmental toxicity, or liver toxicity.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
2-HYDROXYETHYL METHACRYLATE	Dermal	Rabbit	LD50 > 5,000 mg/kg
2-HYDROXYETHYL METHACRYLATE	Ingestion	Rat	LD50 5,564 mg/kg
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA)	Dermal	Professio nal judgeme nt	LD50 estimated to be > 5,000 mg/kg
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA)	Ingestion	Rat	LD50 > 11,700 mg/kg
ETHANOL	Dermal	Rabbit	LD50 > 15,800 mg/kg
ETHANOL	Inhalation- Vapor (4 hours)	Rat	LC50 124.7 mg/l
ETHANOL	Ingestion	Rat	LD50 17,800 mg/kg
2-PROPENOIC ACID, 2-METHYL-, REACTION PRODUCTS WITH 1,10-DECANEDIOL AND PHOSPHOROUS OXIDE (P2O5)	Dermal	Professio nal judgeme nt	LD50 estimated to be > 5,000 mg/kg
2-PROPENOIC ACID, 2-METHYL-, REACTION PRODUCTS WITH 1,10-DECANEDIOL AND PHOSPHOROUS OXIDE (P2O5)	Ingestion	Rat	LD50 > 2,000 mg/kg
COPOLYMER OF ACRYLIC AND ITACONIC ACID	Ingestion	Rat	LD50 > 5,000 mg/kg
COPOLYMER OF ACRYLIC AND ITACONIC ACID	Dermal	similar health hazards	LD50 estimated to be > 5,000 mg/kg
CAMPHORQUINONE	Dermal	Professio nal judgeme nt	LD50 estimated to be 2,000 - 5,000 mg/kg
CAMPHORQUINONE	Ingestion	Rat	LD50 > 2,000 mg/kg
DIMETHYLAMINOBENZOAT(-4)	Dermal	Rat	LD50 > 2,000 mg/kg
DIMETHYLAMINOBENZOAT(-4)	Ingestion	Rat	LD50 > 2,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Overall product	Rabbit	No significant irritation
2-HYDROXYETHYL METHACRYLATE	Rabbit	Minimal irritation
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA)	Rabbit	No significant irritation
ETHANOL	Rabbit	No significant irritation
2-PROPENOIC ACID, 2-METHYL-, REACTION PRODUCTS WITH 1,10-	In vitro	Corrosive
DECANEDIOL AND PHOSPHOROUS OXIDE (P2O5)	data	
DIMETHYLAMINOBENZOAT(-4)	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value

3M TM ESPE TM Scotchbond TM Universal
--

Overall product	In vitro	Corrosive
	data	
2-HYDROXYETHYL METHACRYLATE	Rabbit	Moderate irritant
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA)	In vitro	No significant irritation
	data	
ETHANOL	Rabbit	Severe irritant
2-PROPENOIC ACID, 2-METHYL-, REACTION PRODUCTS WITH 1,10-	In vitro	Corrosive
DECANEDIOL AND PHOSPHOROUS OXIDE (P2O5)	data	
DIMETHYLAMINOBENZOAT(-4)	Rabbit	Mild irritant

Skin Sensitization

Name	Species	Value
2-HYDROXYETHYL METHACRYLATE	Human	Sensitizing
	and	
	animal	
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA)	Mouse	Not classified
ETHANOL	Human	Not classified
2-PROPENOIC ACID, 2-METHYL-, REACTION PRODUCTS WITH 1,10-	Professio	Sensitizing
DECANEDIOL AND PHOSPHOROUS OXIDE (P2O5)	nal	
	judgeme	
	nt	

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
2-HYDROXYETHYL METHACRYLATE	In vivo	Not mutagenic
2-HYDROXYETHYL METHACRYLATE	In Vitro	Some positive data exist, but the data are not sufficient for classification
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA)	In Vitro	Not mutagenic
ETHANOL	In Vitro	Some positive data exist, but the data are not sufficient for classification
ETHANOL	In vivo	Some positive data exist, but the data are not sufficient for classification
2-PROPENOIC ACID, 2-METHYL-, REACTION PRODUCTS WITH 1,10- DECANEDIOL AND PHOSPHOROUS OXIDE (P2O5)	In Vitro	Not mutagenic

Carcinogenicity

· ···· · · · · · · · · · · · · · · · ·							
Name	Route	Species	Value				
ETHANOL	Ingestion	Multiple	Some positive data exist, but the data are not				
		animal	sufficient for classification				
		species					

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
2-HYDROXYETHYL METHACRYLATE	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
2-HYDROXYETHYL METHACRYLATE	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	49 days
2-HYDROXYETHYL METHACRYLATE	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA)	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	during gestation
ETHANOL	Inhalation	Not classified for development	Rat	NOAEL 38 mg/l	during gestation
ETHANOL	Ingestion	Not classified for development	Rat	NOAEL 5,200	premating &

Page 8 **of** 11

3M TM ESPE TM Scotchbond TM Universal	02/21/20

		mg/kg/day	during
			gestation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
ETHANOL	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	LOAEL 2.6 mg/l	30 minutes
ETHANOL	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	LOAEL 9.4 mg/l	not available
ETHANOL	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	NOAEL not available	
ETHANOL	Ingestion	kidney and/or bladder	Not classified	Dog	NOAEL 3,000 mg/kg	
2-PROPENOIC ACID, 2- METHYL-, REACTION PRODUCTS WITH 1,10- DECANEDIOL AND PHOSPHOROUS OXIDE (P2O5)	Inhalation	respiratory irritation	May cause respiratory irritation	similar health hazards	NOAEL Not available	
COPOLYMER OF ACRYLIC AND ITACONIC ACID	Ingestion	nervous system	Not classified	Rat	NOAEL 5,000 mg/kg	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA)	Ingestion	endocrine system hematopoietic system liver heart skin gastrointestinal tract bone, teeth, nails, and/or hair immune system muscles nervous system eyes kidney and/or bladder respiratory system vascular system	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
ETHANOL	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Rabbit	LOAEL 124 mg/l	365 days
ETHANOL	Inhalation	hematopoietic system immune system	Not classified	Rat	NOAEL 25 mg/l	14 days
ETHANOL	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 8,000 mg/kg/day	4 months
ETHANOL	Ingestion	kidney and/or bladder	Not classified	Dog	NOAEL 3,000 mg/kg/day	7 days
COPOLYMER OF ACRYLIC AND ITACONIC ACID	Ingestion	endocrine system hematopoietic system liver	Not classified	Rat	NOAEL 200 mg/kg/day	28 days
COPOLYMER OF ACRYLIC AND ITACONIC ACID	Ingestion	heart bone, teeth, nails, and/or hair immune system muscles nervous system eyes kidney and/or	Not classified	Rat	NOAEL 2,000 mg/kg/day	28 days

Page 9 **of** 11

3M TM ESPE TM Scotchbor	ıd [™] Universal	02/21/20			
		respiratory			
	system	vascular			
	system				

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate uncured product in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. If no other disposal options are available, waste product—that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): D001 (Ignitable), D035 (Methyl ethyl ketone)

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

EPCKA 511/512 mazaru Ciassifications:					
Physical Hazards					
Flammable (gases, aerosols, liquids, or solids)					

Health Hazards
Hazard Not Otherwise Classified (HNOC)
Respiratory or Skin Sensitization

Serious eye damage or eye irritation

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 3 Flammability: 3 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

 Document Group:
 29-8287-4
 Version Number:
 7.02

 Issue Date:
 02/21/20
 Supercedes Date:
 06/05/19

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com

Page 11 **of** 11



Safety Data Sheet

Copyright, 2020, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 27-9483-2
 Version Number:
 4.05

 Issue Date:
 01/27/20
 Supercedes Date:
 04/23/18

SECTION 1: Identification

1.1. Product identifier

6032/6033 3MTM ESPETM FILTEKTM SUPREME ULTRA FLOWABLE RESTORATIVE

Product Identification Numbers

 $70-2010-7758-6, 70-2010-7759-4, 70-2010-7760-2, 70-2010-7761-0, 70-2010-7762-8, 70-2010-7763-6, 70-2010-7764-4, 70-2010-7765-1, 70-2010-7766-9, 70-2010-7767-7, 70-2010-7768-5, 70-2010-7769-3, 70-2010-7771-9\\ 7000128929, 7000128930, 7000128932, 7000128931, 7000128933, 7000128934, 7000128935, 7000128936, 7000128937, 7000128938, 7000128939, 7000128940, 7000128941$

1.2. Recommended use and restrictions on use

Recommended use

Dental product, Composite restorative material

Restrictions on use

For use only by dental professionals

1.3. Supplier's details

MANUFACTURER: 3M

DIVISION: Oral Care Solutions Division

ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA **Telephone:** 1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

2.1. Hazard classification

Skin Sensitizer: Category 1.

2.2. Label elements

Signal word

Page 1 **of** 10

Warning

Symbols

Exclamation mark |

Pictograms



Hazard Statements

May cause an allergic skin reaction.

Precautionary Statements

Prevention:

Avoid breathing dust/fume/gas/mist/vapors/spray.

Wear protective gloves.

Contaminated work clothing must not be allowed out of the workplace.

Response:

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
SILANE TREATED CERAMIC	444758-98-9	50 - 60 Trade Secret *
SUBSTITUTED DIMETHACRYLATE	27689-12-9	15 - 25 Trade Secret *
BISPHENOL A DIGLYCIDYL ETHER	1565-94-2	5 - 10 Trade Secret *
DIMETHACRYLATE (BISGMA)		
SILANE TREATED SILICA	248596-91-0	5 - 10 Trade Secret *
TRIETHYLENE GLYCOL DIMETHACRYLATE	109-16-0	< 10 Trade Secret *
(TEGDMA)		
YTTERBIUM FLUORIDE (YbF3)	13760-80-0	< 5 Trade Secret *
REACTED POLYCAPROLACTONE POLYMER	None	< 2 Trade Secret *
DIPHENYLIODONIUM HEXAFLUOROPHOSPHATE	58109-40-3	< 0.2 Trade Secret *

^{*}The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance
Carbon monoxide
Carbon dioxide

Condition

During Combustion During Combustion

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

A no-touch technique is recommended. If skin contact occurs, wash skin with soap and water. Acrylates may penetrate

01/27/20

commonly-used gloves. If product contacts glove, remove and discard glove, wash hands immediately with soap and water and then re-glove. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not get in eyes.

7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
FLUORIDES	13760-80-0	ACGIH		A4: Not class. as human
				carcin
FLUORIDES	13760-80-0	OSHA	TWA(as dust):2.5	
			mg/m3;TWA(as F):2.5 mg/m3	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

OSHA: United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use in a well-ventilated area.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Skin/hand protection

See Section 7.1 for additional information on skin protection.

Respiratory protection

None required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state Solid Color Tooth

Specific Physical Form: Paste

Page 4 **of** 10

01/27/20

OdorSlight AcrylateOdor thresholdNo Data AvailablepHNot ApplicableMelting pointNo Data AvailableBoiling PointNot ApplicableFlash PointNo flash pointEvaporation rateNot Applicable

Flash Point

Flash Point

Evaporation rate

Flammability (solid, gas)

Flammable Limits(LEL)

Flammable Limits(UEL)

Vapor Pressure

Vapor Density

Not Applicable

Specific Gravity 1.5 [Ref Std: WATER=1]

Solubility in Water Negligible Solubility- non-water No Data Available Partition coefficient: n-octanol/ water Not Applicable **Autoignition temperature** No Data Available No Data Available **Decomposition temperature** No Data Available Viscosity No Data Available Molecular weight **VOC Less H2O & Exempt Solvents** No Data Available

SECTION 10: Stability and reactivity

10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

Substance Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be

relevant to the material as a whole.

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

The information below represents toxicological information associated with the individual components of the uncured

The information below represents toxicological information associated with the individual components of the uncured product. Once properly mixed and/or cured, the product is safe for its intended use.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

This product may have a characteristic odor; however, no adverse health effects are anticipated.

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eve Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE2,000 - 5,000 mg/kg
SILANE TREATED CERAMIC	Dermal		LD50 estimated to be > 5,000 mg/kg
SILANE TREATED CERAMIC	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
SUBSTITUTED DIMETHACRYLATE	Dermal	Professio nal judgeme nt	LD50 estimated to be > 5,000 mg/kg
SUBSTITUTED DIMETHACRYLATE	Ingestion	Rat	LD50 > 17,600 mg/kg
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA)	Dermal	Professio nal judgeme nt	LD50 estimated to be > 5,000 mg/kg
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA)	Ingestion	Rat	LD50 > 11,700 mg/kg
SILANE TREATED SILICA	Dermal		LD50 estimated to be > 5,000 mg/kg
SILANE TREATED SILICA	Ingestion		LD50 estimated to be > 5,000 mg/kg
TRIETHYLENE GLYCOL DIMETHACRYLATE (TEGDMA)	Dermal	Professio nal judgeme nt	LD50 estimated to be > 5,000 mg/kg
TRIETHYLENE GLYCOL DIMETHACRYLATE (TEGDMA)	Ingestion	Rat	LD50 10,837 mg/kg
YTTERBIUM FLUORIDE (YbF3)	Dermal	Professio nal	LD50 estimated to be > 5,000 mg/kg

Page 6 **of** 10

Λ1	/27/20	
VI.	141140	

		judgeme nt	
YTTERBIUM FLUORIDE (YbF3)	Ingestion	Rat	LD50 > 5,000 mg/kg
REACTED POLYCAPROLACTONE POLYMER	Dermal	Professio nal judgeme nt	LD50 estimated to be 2,000 - 5,000 mg/kg
REACTED POLYCAPROLACTONE POLYMER	Ingestion	similar compoun ds	LD50 estimated to be 2,000 - 5,000 mg/kg
DIPHENYLIODONIUM HEXAFLUOROPHOSPHATE	Ingestion	Rat	LD50 32 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
SILANE TREATED CERAMIC	similar	No significant irritation
	compoun	
	ds	
SUBSTITUTED DIMETHACRYLATE	Rabbit	No significant irritation
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA)	Rabbit	No significant irritation
SILANE TREATED SILICA	Professio	No significant irritation
	nal	
	judgeme	
	nt	
TRIETHYLENE GLYCOL DIMETHACRYLATE (TEGDMA)	Guinea	Mild irritant
	pig	
DIPHENYLIODONIUM HEXAFLUOROPHOSPHATE	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
SILANE TREATED CERAMIC	similar	Mild irritant
	compoun	
	ds	
SUBSTITUTED DIMETHACRYLATE	Rabbit	Mild irritant
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA)	In vitro	No significant irritation
	data	
SILANE TREATED SILICA	Professio	No significant irritation
	nal	
	judgeme	
	nt	
TRIETHYLENE GLYCOL DIMETHACRYLATE (TEGDMA)	Professio	Moderate irritant
	nal	
	judgeme	
	nt	
YTTERBIUM FLUORIDE (YbF3)	Professio	Mild irritant
	nal	
	judgeme	
	nt	
DIPHENYLIODONIUM HEXAFLUOROPHOSPHATE	Rabbit	Mild irritant

Skin Sensitization

SKIII SCHSICIZACION		
Name	Species	Value
SILANE TREATED CERAMIC	similar	Not classified
	compoun	
	ds	
SUBSTITUTED DIMETHACRYLATE	Guinea	Not classified
	pig	
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA)	Mouse	Not classified
TRIETHYLENE GLYCOL DIMETHACRYLATE (TEGDMA)	Human	Sensitizing
	and	_
	animal	

01/27/20

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Germ Cen Mutagementy		
Name	Route	Value
SUBSTITUTED DIMETHACRYLATE	In Vitro	Not mutagenic
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA)	In Vitro	Not mutagenic
TRIETHYLENE GLYCOL DIMETHACRYLATE (TEGDMA)	In Vitro	Some positive data exist, but the data are not
		sufficient for classification
DIPHENYLIODONIUM HEXAFLUOROPHOSPHATE	In Vitro	Some positive data exist, but the data are not
		sufficient for classification

Carcinogenicity

Name	Route	Species	Value
SILANE TREATED CERAMIC	Inhalation	similar compoun ds	Some positive data exist, but the data are not sufficient for classification
TRIETHYLENE GLYCOL DIMETHACRYLATE (TEGDMA)	Dermal	Mouse	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure
			~ P		Duration
BISPHENOL A DIGLYCIDYL ETHER	Ingestion	Not classified for development	Rat	NOAEL 1,000	during
DIMETHACRYLATE (BISGMA)				mg/kg/day	gestation
TRIETHYLENE GLYCOL	Ingestion	Not classified for female reproduction	Mouse	NOAEL 1	1 generation
DIMETHACRYLATE (TEGDMA)		_		mg/kg/day	_
TRIETHYLENE GLYCOL	Ingestion	Not classified for male reproduction	Mouse	NOAEL 1	1 generation
DIMETHACRYLATE (TEGDMA)		_		mg/kg/day	
TRIETHYLENE GLYCOL	Ingestion	Not classified for development	Mouse	NOAEL 1	1 generation
DIMETHACRYLATE (TEGDMA)				mg/kg/day	_

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
DIPHENYLIODONIUM HEXAFLUOROPHOSPH ATE	Inhalation	respiratory irritation	Not classified	Not available	Irritation Equivocal	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
SILANE TREATED CERAMIC	Inhalation	pulmonary fibrosis	Not classified	similar compoun ds	NOAEL Not available	
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA)	Ingestion	endocrine system hematopoietic system liver heart skin gastrointestinal tract bone, teeth, nails, and/or hair immune system muscles nervous system eyes kidney and/or bladder respiratory system vascular system	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days

6032/6033 3MTM ESPETM FILTEKTM SUPREME ULTRA FLOWABLE RESTORATIVE

01/27/20

TRIETHYLENE	Dermal	kidney and/or	Not classified	Mouse	NOAEL 833	78 weeks
GLYCOL		bladder blood			mg/kg/day	
DIMETHACRYLATE		·				
(TEGDMA)						

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards

Not applicable

Health Hazards

Respiratory or Skin Sensitization

Additional TSCA Information

Components	CAS No	Additional Information

Page 9 **of** 10

(022/(022 2NT)	M DODDEM DIT TERZEM OUDDEMA	AULTO A DI OULA	DIE DECEODATIVE
0032/ 0033 3 9 **	M ESPETM FILTEKTM SUPREMI	5 ULTKA FLUWA	BLE RESIUKATIVE

01/27/20

SILANE TREATED SILICA	248596-91-0	Allowed use(s): Coating additive.

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group:27-9483-2Version Number:4.05Issue Date:01/27/20Supercedes Date:04/23/18

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com

Page 10 **of** 10



Safety Data Sheet

Copyright,2017,3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group: 26-5783-1 **Version Number:** 6.01 **Issue Date:** 12/29/17 **Supercedes Date:** 08/14/17

SECTION 1: Identification

1.1. Product identifier

6028/6029/5916 3MTM ESPETM FILTEKTM SUPREME ULTRA UNIVERSAL RESTORATIVE

1.2. Recommended use and restrictions on use

Recommended use

Dental Product, Restorative

Restrictions on use

For use only by dental professionals

1.3. Supplier's details

MANUFACTURER: 3M

DIVISION: Oral Care Solutions Division

ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA

Telephone: 1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

2.1. Hazard classification

Skin Sensitizer: Category 1.

2.2. Label elements

Signal word

Warning

Symbols

Exclamation mark

Pictograms

Page 1 of 10



Hazard Statements

May cause an allergic skin reaction.

Precautionary Statements

Prevention:

Avoid breathing dust/fume/gas/mist/vapors/spray.

Wear protective gloves.

Contaminated work clothing must not be allowed out of the workplace.

Response:

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
SILANE TREATED CERAMIC	444758-98-9	60 - 80 Trade Secret *
SILANE TREATED SILICA	248596-91-0	1 - 10 Trade Secret *
DIURETHANE DIMETHACRYLATE (UDMA)	72869-86-4	1 - 10 Trade Secret *
BISPHENOL A POLYETHYLENE GLYCOL	41637-38-1	1 - 10 Trade Secret *
DIETHER DIMETHACRYLATE		
BISPHENOL A DIGLYCIDYL ETHER	1565-94-2	1 - 10 Trade Secret *
DIMETHACRYLATE (BISGMA)		
SILANE TREATED ZIRCONIA	None	1 - 5 Trade Secret *
POLYETHYLENE GLYCOL DIMETHACRYLATE	25852-47-5	< 5 Trade Secret *
Triethylene glycol dimethacrylate	109-16-0	< 1 Trade Secret *

^{*}The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get

Page 2 of 10

medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance
Carbon mono

Carbon monoxide Carbon dioxide

Condition

During Combustion During Combustion

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid breathing of dust created by cutting, sanding, grinding or machining. A no-touch technique is recommended. If skin contact occurs, wash skin with soap and water. Acrylates may penetrate commonly-used gloves. If product contacts glove, remove and discard glove, wash hands immediately with soap and water and then re-glove. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Do not get in eyes.

Page 3 of 10

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

No occupational exposure limit values exist for any of the components listed in Section 3 of this SDS.

8.2. Exposure controls

8.2.1. Engineering controls

Use in a well-ventilated area.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Skin/hand protection

See Section 7.1 for additional information on skin protection.

Respiratory protection

None required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

General Physical Form:Specific Physical Form:
Paste

Odor, Color, Grade: Slight acrylate odor, Tooth colored

Odor threshold No Data Available pН Not Applicable **Melting point** No Data Available **Boiling Point** Not Applicable **Flash Point** No flash point Not Applicable **Evaporation rate** Flammability (solid, gas) Not Classified Flammable Limits(LEL) Not Applicable Flammable Limits(UEL) Not Applicable Vapor Pressure Not Applicable Vapor Density Not Applicable **Density** 1.9 g/cm3

Specific Gravity1.9 [Ref Std:WATER=1]Solubility In WaterNo Data AvailableSolubility- non-waterNo Data AvailablePartition coefficient: n-octanol/ waterNot ApplicableAutoignition temperatureNo Data Available

Decomposition temperatureNo Data Available

Page 4 of 10

12/29/17

ViscosityNo Data AvailableMolecular weightNo Data AvailableVolatile Organic CompoundsNot ApplicableVOC Less H2O & Exempt SolventsNot Applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

Strong oxidizing agents

10.6. Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

The information below represents toxicological information associated with the individual components of the uncured product. Once properly mixed and/or cured, the product is safe for its intended use.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Page 5 of 10

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE2,000 - 5,000 mg/kg
SILANE TREATED CERAMIC	Dermal		LD50 estimated to be > 5,000 mg/kg
SILANE TREATED CERAMIC	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
SILANE TREATED SILICA	Dermal		LD50 estimated to be > 5,000 mg/kg
SILANE TREATED SILICA	Ingestion		LD50 estimated to be > 5,000 mg/kg
BISPHENOL A POLYETHYLENE GLYCOL DIETHER DIMETHACRYLATE	Dermal	Professio nal judgeme nt	LD50 estimated to be > 5,000 mg/kg
DIURETHANE DIMETHACRYLATE (UDMA)	Dermal	Professio nal judgeme nt	LD50 estimated to be > 5,000 mg/kg
BISPHENOL A POLYETHYLENE GLYCOL DIETHER DIMETHACRYLATE	Ingestion	Rat	LD50 > 2,000 mg/kg
DIURETHANE DIMETHACRYLATE (UDMA)	Ingestion	Rat	LD50 > 5,000 mg/kg
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA)	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA)	Dermal	Professio nal judgeme nt	LD50 estimated to be 2,000 - 5,000 mg/kg
SILANE TREATED ZIRCONIA	Dermal		LD50 estimated to be > 5,000 mg/kg
SILANE TREATED ZIRCONIA	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
POLYETHYLENE GLYCOL DIMETHACRYLATE	Dermal		LD50 estimated to be > 5,000 mg/kg
POLYETHYLENE GLYCOL DIMETHACRYLATE	Ingestion	Rat	LD50 > 5,000 mg/kg
Triethylene glycol dimethacrylate	Dermal	Professio nal judgeme nt	LD50 estimated to be > 5,000 mg/kg
Triethylene glycol dimethacrylate	Ingestion	Rat	LD50 10,837 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

NY.	I a •	T X7 1
Name	Species	Value
SILANE TREATED CERAMIC	similar	No significant irritation
	compoun	
	ds	
SILANE TREATED SILICA	Professio	No significant irritation
	nal	
	judgeme	

Page 6 of 10

	nt	
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA)	Not	Minimal irritation
	available	
SILANE TREATED ZIRCONIA	Rabbit	No significant irritation
Triethylene glycol dimethacrylate	Guinea	Mild irritant
	pig	

Serious Eye Damage/Irritation

Name	Species	Value
SILANE TREATED CERAMIC	similar compoun	Mild irritant
	ds	
SILANE TREATED SILICA	Professio	No significant irritation
	nal	
	judgeme	
	nt	
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA)	Not	Moderate irritant
	available	
SILANE TREATED ZIRCONIA	Rabbit	Mild irritant
Triethylene glycol dimethacrylate	Professio	Moderate irritant
	nal	
	judgeme	
	nt	

Skin Sensitization

Name	Species	Value
SILANE TREATED CERAMIC	similar	Not classified
	compoun	
	ds	
BISPHENOL A POLYETHYLENE GLYCOL DIETHER	Guinea	Not classified
DIMETHACRYLATE	pig	
DIURETHANE DIMETHACRYLATE (UDMA)	Guinea	Sensitizing
	pig	
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA)	Guinea	Sensitizing
	pig	-
Triethylene glycol dimethacrylate	Human	Sensitizing
	and	
	animal	

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
BISPHENOL A POLYETHYLENE GLYCOL DIETHER DIMETHACRYLATE	In Vitro	Not mutagenic
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA)	In Vitro	Some positive data exist, but the data are not sufficient for classification
SILANE TREATED ZIRCONIA	In Vitro	Some positive data exist, but the data are not sufficient for classification
Triethylene glycol dimethacrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

curemogeniery			
Name	Route	Species	Value
SILANE TREATED CERAMIC	Inhalation	similar compoun ds	Some positive data exist, but the data are not sufficient for classification
SILANE TREATED ZIRCONIA	Inhalation	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
Triethylene glycol dimethacrylate	Dermal	Mouse	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA)	Ingestion	Not classified for female reproduction	Mouse	NOAEL 0.8 mg/kg/day	premating & during gestation
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA)	Ingestion	Not classified for male reproduction	Mouse	NOAEL 0.8 mg/kg/day	premating & during gestation
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA)	Ingestion	Not classified for development	Mouse	NOAEL 0.8 mg/kg/day	premating & during gestation
Triethylene glycol dimethacrylate	Ingestion	Not classified for female reproduction	Mouse	NOAEL 1 mg/kg/day	1 generation
Triethylene glycol dimethacrylate	Ingestion	Not classified for male reproduction	Mouse	NOAEL 1 mg/kg/day	1 generation
Triethylene glycol dimethacrylate	Ingestion	Not classified for development	Mouse	NOAEL 1 mg/kg/day	1 generation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

For the component/components, either no data are currently available or the data are not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
SILANE TREATED CERAMIC	Inhalation	pulmonary fibrosis	Not classified	similar compoun ds	NOAEL Not available	
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA)	Ingestion	endocrine system liver nervous system kidney and/or bladder	Not classified	Mouse	NOAEL 0.8 mg/kg/day	premating & during gestation
SILANE TREATED ZIRCONIA	Inhalation	pulmonary fibrosis	Not classified	Multiple animal species	NOAEL Not available	
SILANE TREATED ZIRCONIA	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
Triethylene glycol dimethacrylate	Dermal	kidney and/or bladder blood	Not classified	Mouse	NOAEL 833 mg/kg/day	78 weeks

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

> Page 8 of 10

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards	
Not applicable	

Health Hazards

Respiratory or Skin Sensitization

Additional TSCA Information

Components	CAS No	Consent Order/SNUR
SILANE TREATED SILICA	248596-91-0	Allowed use(s): Coating additive.

15.2. State Regulations

Contact 3M for more information.

California Proposition 65

<u>Ingredient</u>	<u>C.A.S. No.</u>	Classification	
Toluene	108-88-3	Developmental Toxin	

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm

15.3. Chemical Inventories

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

Page 9 **of** 10

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

 Document Group:
 26-5783-1
 Version Number:
 6.01

 Issue Date:
 12/29/17
 Supercedes Date:
 08/14/17

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued.3MMAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3Mproduct is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3Mproduct, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3Mproduct to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3Mprovides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information,3Mmakes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from3M

3M USA SDSs are available at www.3M.com

Page 10 of

10