Page: 1/10

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: March 08, 2018 Revision: March 08, 2018

1 Identification

· Product identifier

· Trade name: Eco-Mastic (White)

Product code: 55-80

· Recommended use and restriction on use

· Recommended use: Coating

· Restrictions on use: No relevant information available.

Details of the supplier of the Safety Data Sheet

· Manufacturer/Supplier:

Mon-Eco Industries, Inc.

5 Joanna Ct.

East Brunswick, NJ 08816 Phone: 732-257-7942

· Emergency telephone number:

ChemTel Inc.

(800)255-3924 (North America) +1 (813)248-0585 (International)



2 Hazard(s) identification

· Classification of the substance or mixture

Eye Irrit. 2A H319 Causes serious eye irritation.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms:



GHS07

· Signal word: Warning · Hazard statements:

H319 Causes serious eye irritation.

Precautionary statements:

P264 Wash thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

Other hazards There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Components:

(Cont'd. on page 2)

Page: 2/10

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: March 08, 2018 Revision: March 08, 2018

Trade name: Eco-Mastic (White)

	(Cont'd. of page 1
1317-65-3 limestone	<20%
9002-93-1 polyethylene glycol	octylphenol ether <2.5% 18 302; Skin Irrit. 2, H315
9036-19-5 polyethylene glycol Eye Dam. 1, H3 1 Acute Tox. 4, H	
13463-67-7 titanium dioxide	<2.5%
57-55-6 propylene glycol	<2.5%
9004-34-6 cellulose	<2.5%
9016-45-9 nonylphenol, ethox	5; Eye Irrit. 2A, H319
14808-60-7 quartz	<1%

· Additional information:

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret. Non-classification as a carcinogen is based on non-inhalable form of product. IARC listings for quartz and titanium dioxide note that the substance must be respirable.

For the wording of the listed Hazard Statements, refer to section 16.

4 First-aid measures

Description of first aid measures

· After inhalation:

Respiration of particulates is unlikely during normal usage.

Supply fresh air; consult doctor in case of complaints.

Provide oxygen treatment if affected person has difficulty breathing.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment in case of complaints.

· After eye contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

· Most important symptoms and effects, both acute and delayed:

Headache

Dizziness

Gastric or intestinal disorders when ingested.

Nausea in case of ingestion.

Irritating to eyes.

Indication of any immediate medical attention and special treatment needed:

No relevant information available.

5 Fire-fighting measures

Extinguishing media

(Cont'd. on page 3)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: March 08, 2018 Revision: March 08, 2018

Trade name: Eco-Mastic (White)

(Cont'd. of page 2)

· Suitable extinguishing agents:

Foam

Fire-extinguishing powder

Gaseous extinguishing agents

Carbon dioxide

- · For safety reasons unsuitable extinguishing agents: None.
- Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- Advice for firefighters
- Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

Wear protective equipment. Keep unprotected persons away.

Environmental precautions

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

· Methods and material for containment and cleaning up

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Send for recovery or disposal in suitable receptacles.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling
- · Precautions for safe handling:

Use only in well ventilated areas.

Avoid splashes or spray in enclosed areas.

Avoid contact with the eyes and skin.

Prevent formation of dust.

Handle with care.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- Requirements to be met by storerooms and receptacles:

Avoid storage near extreme heat, ignition sources or open flame.

Store in cool, dry conditions in well sealed receptacles.

Do not allow product to freeze.

· Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidizing agents.

(Cont'd. on page 4)

Page: 4/10

Safety Data Sheet acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: March 08, 2018 Revision: March 08, 2018

Trade name: Eco-Mastic (White)

· Specific end use(s) No relevant information available.

(Cont'd. of page 3)

. -	
B Exposure co	ontrols/personal protection
· Control parar	
•	vith limit values that require monitoring at the workplace:
1317-65-3 limes	
PEL (USA)	Long-term value: 15* 5** mg/m³ *total dust **respirable fraction
REL (USA)	Long-term value: 10* 5** mg/m³ *total dust **respirable fraction
TLV (USA)	TLV withdrawn
13463-67-7 tita	nium dioxide
PEL (USA)	Long-term value: 15* mg/m³ *total dust
REL (USA)	See Pocket Guide App. A
TLV (USA)	Long-term value: 10 mg/m³ withdrawn from NIC
EL (Canada)	Long-term value: 10* 3** mg/m³ *total dust;**respirable fraction; IARC 2B
EV (Canada)	Long-term value: 10 mg/m³ total dust
LMPE (Mexico)	Long-term value: 10 mg/m³ A4
57-55-6 propyle	ene glycol
WEEL (USA)	Long-term value: 10 mg/m³
EV (Canada)	Long-term value: 155* 10** mg/m³, 50* ppm *vapour and aerosol;**aerosol only
9004-34-6 cellu	ilose
PEL (USA)	Long-term value: 15* 5** mg/m³ *total dust **respirable fraction
REL (USA)	Long-term value: 10* 5** mg/m³ *total dust **respirable fraction
TLV (USA)	Long-term value: 10 mg/m³
EL (Canada)	Long-term value: 10* 3** mg/m³ *total dust, **respirable fraction
EV (Canada)	Long-term value: 10 mg/m³ paper fibre, total dust
LMPE (Mexico)	Long-term value: 10 mg/m³
14808-60-7 qua	artz
PEL (USA)	see Quartz listing
REL (USA)	Long-term value: 0.05* mg/m³ *respirable dust; See Pocket Guide App. A
	(Cont'd. on pag

Page: 5/10

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: March 08, 2018 Revision: March 08, 2018

Trade name: Eco-Mastic (White)

		(Cont'd. of page 4)
TLV (USA)	Long-term value: 0.025* mg/m³ *as respirable fraction	
EL (Canada)	Long-term value: 0.025 mg/m³ ACGIH A2; IARC 1	
EV (Canada)	Long-term value: 0.10* mg/m³ *respirable fraction	
LMPE (Mexico)	Long-term value: 0.025* mg/m³ A2, *fracción respirable	

• Exposure controls

General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid breathing mist, vapors, or spray.

Do not breathe dust.

Avoid contact with the eyes and skin.

- · Engineering controls: No relevant information available.
- · Breathing equipment:

NIOSH or EU approved dust respirator should be used for operations generating dust.

Use suitable respiratory protective device in case of insufficient ventilation.

For spills, respiratory protection may be advisable.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Eve protection:



Safety glasses

- · Body protection: Protective work clothing
- · Limitation and supervision of exposure into the environment

No relevant information available.

· Risk management measures No relevant information available.

9 Physical and chemical properties

- Information on basic physical and chemical properties
- · Appearance:

Form: Liquid Color: White Odor: Mild

· Odor threshold: Not determined.

(Cont'd. on page 6)

Page: 6/10

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: March 08, 2018 Revision: March 08, 2018

Trade name: Eco-Mastic (White)

		(Cantlel of none
		(Cont'd. of page
pH-value:	Not determined.	
Melting point/Melting range:	Not determined.	
· Boiling point/Boiling range:	Not determined.	
· Flash point:	Not applicable.	
· Flammability (solid, gaseous):	Not applicable.	
· Auto-ignition temperature:	Not determined.	
· Decomposition temperature:	Not determined.	
· Danger of explosion:	Product does not present an explosion hazard.	
· Explosion limits		
Lower:	Not determined.	
Upper:	Not determined.	
· Oxidizing properties:	Non-oxidizing.	
· Vapor pressure:	Not determined.	
· Density:		
Relative density:	1.35	
Vapor density:	Not determined.	
Evaporation rate:	Not determined.	
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/wa	ter): Not determined.	
· Viscosity		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Other information	No relevant information available.	

10 Stability and reactivity

- · Reactivity: No relevant information available.
- · Chemical stability:
- · Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

Possibility of hazardous reactions

Toxic fumes may be released if heated above the decomposition point.

Reacts with strong acids and oxidizing agents.

- · Conditions to avoid Excessive heat.
- Incompatible materials

Strong acids

Oxidizers

· Hazardous decomposition products Carbon monoxide and carbon dioxide

Page: 7/10

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: March 08, 2018 Revision: March 08, 2018

Trade name: Eco-Mastic (White)

(Cont'd. of page 6)

11 Toxicological information

- Information on toxicological effects
- · Acute toxicity: Based on available data, the classification criteria are not met.
- · LD/LC50 values that are relevant for classification:

9002-93-1 polyethylene glycol octylphenol ether

Oral LD50 1800 mg/kg (rat)

- Primary irritant effect:
- · On the skin: Based on available data, the classification criteria are not met.
- · On the eve: Irritating effect.
- · Sensitization: No sensitizing effects known.

· IARC (International Agency for Research on Cancer):		
13463-67-7	titanium dioxide	2B
14808-60-7	quartz	1
1897-45-6	chlorothalonil (ISO)	2B

· NTP (National Toxicology Program):

14808-60-7 quartz

K

· OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

· Probable route(s) of exposure:

Ingestion.

Eve contact.

Skin contact.

- · Germ cell mutagenicity: Based on available data, the classification criteria are not met.
- · Carcinogenicity:

Contains known or suspect carcinogens when inhaled. Product is in non-inhalable form and is nonclassifiable as a carcinogen.

- Reproductive toxicity: Based on available data, the classification criteria are not met.
- STOT-single exposure: Based on available data, the classification criteria are not met.
- · STOT-repeated exposure: Based on available data, the classification criteria are not met.
- · Aspiration hazard: Based on available data, the classification criteria are not met.

12 Ecological information

- · Toxicity
- · Aquatic toxicity

Harmful to aquatic life with long lasting effects.

9002-93-1 polyethylene glycol octylphenol ether		
EC50	26 mg/kg (daphnia)	
LC50	9.6 mg/l (pimephales promelas)	
9036-19-5 polyethylene glycol octylphenyl ether		

- Total to a polyculylene glycol octylphenyl culer
- EC50 4.8-8.9 mg/l (pimephales promelas) (static test, 96H)
- · Persistence and degradability No relevant information available.
- · Bioaccumulative potential: No relevant information available.

(Cont'd. on page 8)

Page: 8/10

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: March 08, 2018 Revision: March 08, 2018

Trade name: Eco-Mastic (White)

(Cont'd. of page 7)

- · Mobility in soil: No relevant information available.
- Additional ecological information
- · General notes:

Avoid transfer into the environment.

Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.

- · Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.
- · Other adverse effects No relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

- Uncleaned packagings
- Recommendation: Disposal must be made according to official regulations.

14 Transport information		
· UN-Number · DOT, ADR, IMDG, IATA	Not regulated.	
· UN proper shipping name · DOT, ADR, IMDG, IATA	Not regulated.	
· Transport hazard class(es)		
· DOT, ADR, IMDG, IATA · Class	Not regulated.	
· Packing group · DOT, ADR, IMDG, IATA	Not regulated.	
· Environmental hazards · Marine pollutant:	No	
· Special precautions for user	Not applicable.	
Transport in bulk according to Annex MARPOL73/78 and the IBC Code	II of Not applicable.	

Page: 9/10

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: March 08, 2018 Revision: March 08, 2018

Trade name: Eco-Mastic (White)

(Cont'd. of page 8)

15 Regulatory	information
---------------	-------------

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- · United States (USA)
- ·SARA
- · Section 302 (extremely hazardous substances):

None of the ingredients are listed.

Section 355 (extremely hazardous substances):

None of the ingredients are listed.

Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

· TSCA (Toxic Substances Control Act)

All ingredients are listed.

· Proposition 65 (California)

13463-67-7	titanium dioxide

12174-11-7 Attapulgite (Palygorskite)

14808-60-7 quartz

1897-45-6 chlorothalonil (ISO)

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

67-56-1 methanol

EPA (Environmental Protection Agency):

None of the ingredients are listed.

IARC (International Agency for Research on Cancer):

13463-67-7	titanium dioxide	2B
14808-60-7	quartz	1
1897-45-6	chlorothalonil (ISO)	2B

NIOSH-Ca (National Institute for Occupational Safety and Health):

	titanium dioxide
14808-60-7	quartz

Canadian Domestic Substances List (DSL):

All ingredients are listed.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any

(Cont'd. on page 10)

Page: 10/10

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: March 08, 2018 Revision: March 08, 2018

Trade name: Eco-Mastic (White)

(Cont'd. of page 9)

specific product features and shall not establish a legally valid contractual relationship.

· Date of preparation / last revision March 08, 2018 / -

· Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistant, Bio-accumulable, Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety and Health

OSHA: Occupational Safety & Health Administration Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Sources

Website, European Chemicals Agency (echa.europa.eu)

Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/ overview/home.do)

Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com