

## <u>Weekly Safety Meeting</u> Job Site Hazards - Falls

Date:	Jobsite:
-------	----------

Discussion Leader:	Summary
	Wily Coyote always seems to fall into a deep canyon and not be injured at all. People can't. Then why do we seem to have trouble
Attendance Sign- In:	getting workers to pay attention to the fall hazards around them?  Guide for Discussion
-	
	The following items represent the bulk of the exposure to falls on a construction site.
	Ladders:
	Always use the right ladder.
	Set them on level ground and tie them off at the top (for security).
	— Do not over reach.
	Do not over extend yourself on the ladder.
	Always face the ladder and try to use both hands when climbing.
	Floor Openings:
	Floor openings should be properly covered.
	Covers must be able to support walls the same as the floor.
	—— Covers should be firmly attached to the floor/walking/working surface.
	Covers should be marked as such. For example: "Cover," or "Do Not Remove Floor Opening Cover."
	Consider wall openings and uncompleted stairways as openings with suitable protection provided.
	Stairways:
	Use handrails.
	Watch where you step.
	—— Keep your view clear.
	Concentrate on the stairs.
	Do not run up or down the stairs.
	Keep stair well clean.
	——   Housekeeping:
	——   Always try to provide good footing.
	—— Keep tools, trash, scrap materials out of walkways.
	Clean as you go.
	Always be wary of oil, ice or snow.
	Additional Discussion Notes:
<del></del>	Balance. Wear appropriate footwear (including auxiliary footwear like corkers) when necessary.
	Domambar
	Remember  Paying attention to things around you like ladders floor openings stairneys and good housekeening will halp provent a fall.
	Paying attention to things around you like ladders, floor openings, stairways and good housekeeping will help prevent a fall.